



DIN 6325/ISO 8734

Tolerance m5

Hårdhed: 60 +/- 2 HRC

Bestillingsnr.: CYL 6325-d x L

| Ø/d | 1,0 | 1,5 | 2,0 | 2,5 | 3,0 | 4,0 | 5,0 | 6,0 | 8,0 | 10,0 | 12,0 | 13,0 | 14,0 | 16,0 | 18,0 | 20,0 | 25,0 |
|-----|---------------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|
| L | Pris pr. stk. | | | | | | | | | | | | | | | | |
| 6 | | | | | | - | - | - | - | - | - | - | - | - | - | - | - |
| 8 | | | | | | | | - | - | - | - | - | - | - | - | - | - |
| 10 | | | | | | | | | - | - | - | - | - | - | - | - | - |
| 12 | | | | | | | | | | - | - | - | - | - | - | - | - |
| 14 | - | | | | | | | | | | - | - | - | - | - | - | - |
| 16 | | | | | | | | | | | | - | - | - | - | - | - |
| 18 | - | - | | | | | | | | | | - | - | - | - | - | - |
| 20 | | | | | | | | | | | | - | - | - | - | - | - |
| 22 | - | - | - | - | | | | | | | | - | - | - | - | - | - |
| 24 | - | | | | | | | | | | | | - | - | - | - | - |
| 28 | - | - | | | | | | | | | | | | - | - | - | - |
| 30 | - | - | - | - | | | | | | | | | | | - | - | - |
| 32 | - | - | | | | | | | | | | | | | - | - | - |
| 36 | - | - | | | | | | | | | | | | | - | - | - |
| 40 | - | - | | | | | | | | | | | | | | - | - |
| 45 | - | - | - | - | | | | | | | | | | | - | - | - |
| 50 | - | - | - | - | | | | | | | | | | | | - | - |
| 55 | - | - | - | - | | | | | | | | | | | - | - | - |
| 60 | - | - | - | - | | | | | | | | | | | | - | - |
| 70 | - | - | - | - | - | | | | | | | | | | | - | - |
| 80 | - | - | - | - | - | | | | | | | | | | | - | - |
| 90 | - | - | - | - | - | - | - | | | | | | | | | - | - |
| 100 | - | - | - | - | - | - | - | | | | | | | | | - | - |
| 120 | - | - | - | - | - | - | - | | | | | | | | | - | - |
| 130 | - | - | - | - | - | - | - | - | - | | | - | | | | - | - |
| 140 | - | - | - | - | - | - | - | - | - | | | | | | | - | - |
| 150 | - | - | - | - | - | - | - | - | - | | | - | | | - | - | - |
| 160 | - | - | - | - | - | - | - | - | - | | | | | | | - | - |